

Product Specifications

Part Number: **CGS-4232-NB1-PC-D024**



Description:

Title: VALVE, FOUR-WAY

Actuator(s): Solenoid, Spring Return

Function: 4-way, 2-position

Body: NAMUR Mount

Media: Air - Inert Gas 15-115 psi 1.03-7.93 bar
Flow: 0.750 Cv

Materials of Construction

Body: Aluminum
Seals: FKM
Weight: 0.9 lb
 0.4 kg


Maintenance & Documentation

Repair kit:	C-4222-SP
Replacement operator:	E5-3198-34-PC-D024
Drawing:	GCS-0209 GEO GMO-0002 Options_manual_ovrd GSL-0002 Options_sol_exh
Operation & Installation:	
Catalog:	NAMUR

Solenoid Specifications



Description:	General Purpose - C5 Class
Operating voltage:	24V DC ±10%
Power (nominal):	7 w
Inrush:	320 mA
Holding:	320 mA
Resistance:	75 ohms
Ingress Protection:	NEMA 4X
Coil class:	F
Duty cycle:	Continuous Duty
Protection:	General purpose
Certification:	CSA / UL



Operator Construction

Solenoid housing material:	Steel - Plated
Solenoid seal material:	Buna
Coil:	Epoxy Molded
Solenoid Connection:	1/2" NPT female conduit with 24" wires